DATASHEET

RIM VENT FOR BULK STORAGE TANKS

CNC 104 Rim Vent

104

APPLICATION

Motherwell Tank Protection (MTP) range of Rim Vents are designed for pressure relief use on low pressure storage tanks. This was originally developed for use as a rim vent on floating roof tanks.

BENEFITS

- Robust construction to cope with regular use.
- **Low cost**
- Fitted with stainless steel screen mesh to prevent corrosion and the ingress of foreign matter.
- Can be flanged or threaded connection.
- ATEX approved to directive 94/9/EC

PHYSICAL

Model	104
Sizes	6"
Process Connection	1. ANSI 150# (Standard) 2. Screwed 3. Special (Flange drilling as required)
Material (Body, cover & pallet)	1. Aluminium

PROCESS

Pressure Setting	Pressure = 0.865"wg (2.15mbar)

ORDERING CODE

MODEL-SIZE-PROCESS CONNECTION-MATERIAL

e.g. 104-06-11 (104 series, 6" ANSI 150#connection, aluminium body)

AFTER SALES SUPPORT

MTP provide comprehensive spares support, a **free valve inspection service** and term preventative maintenance schemes using product-trained technicians to service MTP and other brands of valves and fittings.

mail@sightflow.com.au
Tel: 1800 539220
Mob: 0400 938611